



H-Series Classic 48-2HCX

Plug-in power.

From hauling to towing to security duty, we have the plug-in utility vehicles to meet all your industrial and commercial needs. These cars come standard with material-handling grade Curtis controllers and advanced DC motors built for heavy loads. The HCX can be outfitted with a dumping utility box, shelved enclosed box, flat bed, or stake box.



Classic 48-2HCX
Dumping utility box



Classic 48-2HCX-EB



Classic 48-2HCX-SB



Classic 48-2HCX-FB

Options

- LSV (NEV) Street Legal Package
- AC system upgrade
- Amber strobe light
- Rust-proof chassis treatment
- Lockable glove box
- Extended roof or no roof (see reverse side for details)
- AS1 glass windshield
- Windshield wiper
- Enclosure
- Lester on-board charger

	ALMOND PEARL
	METALLIC SILVER*
	BLACK
	RED
	NAVY BLUE
	WHITE
	METALLIC GREEN
	YELLOW*

*Extra charge for yellow and metallic silver.

Specifications for Classic 48-2HCX, Classic 48-2HCX-EB, Classic 48-2HCX-FB, Classic 48-2HCX-SB*

	Standard	Extended Roof	No Roof
Passengers	2		
Battery System	8x6 V, Trojan T-105		
Motor Power	5.5 hp Continuous ADC		
Controller Power	400 A, Curtis 1268		
Top Speed	19.5 mph (20-25 if LSV)		
Load Capacity	960 lbs		
Cargo Load Capacity	600 lbs		
Dimensions (L x W x H)	2HCX: 132" x 47" x 73" -EB: 129" x 47" x 73" -FB: 123" x 47" x 73" -SB: 128" x 47" x 73"	2HCX: 132" x 47" x 78" -FB: 123" x 47" x 78" -SB: 128" x 47" x 78"	2HCX: 132" x 47" x 50" -EB: 129" x 47" x 70" -FB: 123" x 47" x 50" -SB: 128" x 47" x 50"
Cargo Box Dimensions	48-2HCX: 54"L x 43"W x 9.5"H -EB: 48"L x 46.5"W x 38"H -FB: 48"L x 44"W x 1.5"H -SB: 49"L x 43"W x 19"H		
Weight with Batteries	2HCX: 1500 lbs -EB: 1600 lbs -FB: 1500 lbs -SB: 1520 lbs	2HCX: 1525 lbs -FB: 1525 lbs -SB: 1545 lbs	2HCX: 1465 lbs -EB: 1565 lbs -FB: 1465 lbs -SB: 1485 lbs
Ground Clearance	5"		
Turning Radius	12 ft		
Wheel Base	96"		
Top Climbing Grade	20%		
Body Material	Plastic		
Front and Rear Suspension	Leaf spring and shock		
Steering System	Rack and pinion		
Brake System	Hydraulic		
Tire Size	20.5x8-10, 6-ply DOT		
Tire Pressure	50 psi		
Wheel Type	10" aluminum		
Roof	Molded plastic or Fiberglass (Extended Roof)		
Drive Train	Direct rear drive with 10.25:1 ratio		
Voltage Reducer	20 A, 48V to 12 V included		
Windshield	Foldable tinted		
Seat Belts	2-point seat belts		
Battery Box	Included for center 6 batteries		
Warranty	Four year limited warranty, two year bumper-to-bumper warranty, less wear items		

Features: Headlights, Taillights, Brake lights, Turning signals, Horn, Reverse beeper, Battery indicator, High/Low speed switch, Automatic battery charger (US-made DPI charger)

Options

	Standard Roof	Extended Roof	No Roof
Utility Box	 Classic 48-2HCX	 Classic 48-2HCX-X	 Classic 48-2HCX-NR
Enclosed Box	 Classic 48-2HCX-EB	N/A	 Classic 48-2HCX-EB-NR
Flat Bed	 Classic 48-2HCX-FB	 Classic 48-2HCX-FB-X	 Classic 48-2HCX-FB-NR
Stake Box	 Classic 48-2HCX-SB	 Classic 48-2HCX-SB-X	 Classic 48-2HCX-SB-NR

Your Local STAR EV Dealer:



Golf Carts of Central Florida
407-657-1108

*Specs are subject to change without notification.