



## H-Series Classic 48-4HCX

# Plug-in power.

From hauling to towing to security duty, we have the plug-in utility vehicles to meet all your industrial and commercial needs. These cars come standard with material-handling grade Curtis controllers and advanced DC motors built for heavy loads. The HCX can be outfitted with a dumping utility box, shelved enclosed box, flat bed, or stake box.



Classic 48-4HCX

*\*Optional street legal windshield shown.*



Classic 48-4HCX-EB



Classic 48-4HCX-SB



Classic 48-4HCX-FB

### Options

- LSV (NEV) Street Legal Package
- AC system upgrade
- Amber strobe light
- Rust-proof chassis treatment
- Lockable glove box
- Extended roof or no roof (see reverse side for details)
- AS1 glass windshield (shown)
- Windshield wiper
- Enclosure
- Lester on-board charger

	ALMOND PEARL
	METALLIC SILVER*
	BLACK
	RED
	NAVY BLUE
	WHITE
	METALLIC GREEN
	YELLOW*

*\*Extra charge for yellow and metallic silver.*

**Specifications for Classic 48-4HCX, Classic 48-4HCX-EB, Classic 48-4HCX-FB, Classic 48-4HCX-SB\***

	Standard	Extended Roof	No Roof
Passengers	4		
Battery System	8x6 V, Trojan T-105		
Motor Power	5.5 hp Continuous ADC		
Controller Power	400 A, Curtis 1268		
Top Speed	19.5 mph (20-25 if LSV)		
Load Capacity	1290 lbs		
Cargo Load Capacity	800 lbs		
Dimensions (L x W x H)	4HCX: 162" x 47" x 78" -EB: 159" x 47" x 78" -FB: 153" x 47" x 78" -SB: 156" x 47" x 78"	4HCX: 162" x 47" x 80" -FB: 153" x 47" x 80" -SB: 156" x 47" x 80"	4HCX: 162" x 47" x 50" -EB: 159" x 47" x 69" -FB: 153" x 47" x 50" -SB: 159" x 47" x 50"
Cargo Box Dimensions	48-4HCX: 54"L x 43"W x 9.5"H -EB: 48"L x 46.5"W x 38"H -FB: 48"L x 44"W x 1.5"H -SB: 49"L x 43"W x 19"H		
Weight with Batteries	4HCX: 1625 lbs -EB: 1725 lbs -FB: 1625 lbs -SB: 1645 lbs	4HCX: 1650 lbs -FB: 1650 lbs -SB: 1670 lbs	4HCX: 1575 lbs -EB: 1650 lbs -FB: 1575 lbs -SB: 1595 lbs
Ground Clearance	5"		
Turning Radius	15 ft		
Wheel Base	125"		
Top Climbing Grade	20%		
Body Material	Plastic		
Front and Rear Suspension	Leaf spring and shock		
Steering System	Rack and pinion		
Brake System	Hydraulic		
Tire Size	20.5x8-10, 6-ply DOT		
Tire Pressure	50 psi		
Wheel Type	10" aluminum		
Roof	Molded plastic or Fiberglass (Extended Roof)		
Drive Train	Direct rear drive with 12.49:1 ratio		
Voltage Reducer	20 A, 48V to 12 V included		
Windshield	Foldable tinted		
Seat Belts	2-point seat belts		
Battery Box	Included for center 6 batteries		
Warranty	Four year limited warranty, two year bumper-to-bumper warranty, less wear items		

**Features:** Brush guard, Fender flares, Headlights, Taillights, Brake lights, Turning signals, Horn, Reverse beeper, Battery indicator, High/Low speed switch, Automatic battery charger

**Options**

	Standard Roof	Extended Roof	No Roof
Utility Box			
	Classic 48-4HCX	Classic 48-4HCX-X	Classic 48-4HCX-NR
Enclosed Box		N/A	
	Classic 48-4HCX-EB		Classic 48-4HCX-NR-EB
Flat Bed			
	Classic 48-4HCX-FB	Classic 48-4HCX-FB-X	Classic 48-4HCX-FB-NR
Stake Box			
	Classic 48-4HCX-SB	Classic 48-4HCX-SB-X	Classic 48-4HCX-SB-NR

**Your Local STAR EV Dealer:**



**Golf Carts of Central Florida**  
**407-657-1108**

\*Specs are subject to change without notification.